

## DEFINING THE CHARACTERISTICS AND PERFORMANCE OF GAS LIFT PLUNGERS

James F. Lea and Lawrence N. Mower

Amoco Production Research

### SUMMARY

A laboratory investigation was conducted to provide data necessary to better predict the behavior of gas lift plungers. The laboratory phase of the study was necessary since no data was available on full size commercially available plungers. A test well was instrumented to provide pressure, velocity, and volumetric information during the fall and rise cycle of a variety of commercially available plungers. A data bank representing 132 individual runs has been compiled and behavior of 13 different plunger configurations has been characterized by gas slippage, liquid fallback, and fall velocity. Performance characteristics of the individual plungers has been incorporated in a modified Foss and Gaul<sup>2</sup> mathematical model which provides predicted minimum casing pressure in close agreement with actual laboratory tests. The laboratory data should provide a basis for improved plunger selection and design.

As a second part of the evaluation program, actual field data was collected and the correlations developed for the laboratory tests were finally adjusted to fit field data. The field data was collected from four field locations with a variety of operating conditions. The final correlations and equations describing plunger lift operations have been included in a computer program that can be used for design and analysis of plunger lift operations.

### INTRODUCTION

Plunger lift is an artificial lift method which incorporates a plunger or piston traveling up and down in the production tubing string and utilizes expanding gas energy for its upward movement. This lift method is used in intermittent lift of high GLR oil wells, deliquescence of gas wells, improved efficiency of intermittent gas lift wells, and for removal of paraffin and scale from wells. The plunger provides a partial seal between gas and liquid, reduces liquid fallback, and more efficiently uses gas lift energy.

A review of literature indicated the paucity of laboratory quality data which would adequately describe the expected behavior of full scale commercially available gas lift plungers. A cooperative test program was developed with Camco, Inc., and Ferguson-Beauregard, Inc., which would provide an adequate data base to predict and validate performance of actual plungers.

The initial phase of the project was a laboratory investigation which was intended to improve our understanding and efficiency of utilization of this artificial lift method. A 735-ft laboratory test well was instrumented to provide carefully controlled conditions of pressure, temperature and volumes needed to provide a valid data base on which to accomplish these objectives. Next, a series of field tests were made to compare laboratory correlations to actual field data.

After correlation of the field data, a computer program for calculating the needed parameters was developed with the field corrected laboratory correlations for slip and fallback. The program contains equations similar to a previous model developed by Foss & Gaul<sup>2</sup> of Shell Oil Company. In addition to using correlations developed in this test program, the equations include accounting for the gas produced during the plunger cycle.

## CONCLUSIONS

Laboratory test data have clearly demonstrated that some gas slippage from under the plunger into the liquid slug above the plunger occurs with liquid removal. Total gas slippage generally decreases as plunger velocity increases, and liquid fallback increases as velocity increases. The minimum operating velocity under laboratory conditions was about 250 ft/min. The optimum plunger rise velocity (considering slip and fallback) is plunger dependent although it is near 1000 fpm for most plungers tested. A mathematical model, incorporating the slip and fallback characteristics determined in the laboratory tests, accurately matched the test conditions. It was found that laboratory developed correlations required some adjustment before the program would provide results that matched field data.

Comparison of the plunger model to field data is presently limited to only a few tests. Additional field data will be collected to verify (or indicate the need for further adjustment of) the model and correlations developed. The field data measured to date indicates less pressure necessary to operate with plunger lift than would have been predicted by a model based solely on the laboratory test results.

## DISCUSSION OF LABORATORY TESTS

### Description of Laboratory Experimental Facilities

Test facilities employed during the plunger lift evaluation are shown on Figure 1. Four specially designed mandrels, each containing a Validyne DP-15 pressure transducer, were spaced at approximately 179 ft intervals from a 715 ft depth to 179 ft. The mandrels were connected by hydraulic hose to provide a conduit for the transducer signal wiring. In addition, transducers were installed to measure surface casing and tubing pressure. The downhole temperature was measured with a copper-constantan thermocouple. Static and differential pressure transducers mounted on flange taps provided gas measurement during the production cycle.

The liquid slug volume, during downhole placement, was determined by a Rockwell 5/8 in. S-04 water meter, and also by a change in differential pressure indicated by a Validyne DP-15 Transducer located at the bottom of the separator. The transducer provided a dynamic indication of produced liquid volumes during the production cycle.

Raw data were processed via a statistical analysis program to provide graphical output of pressure response during fall and rise cycles.

### Plunger Types Evaluated

Twelve plunger types were evaluated in the laboratory test program. This selection of plungers more than adequately covers the types of designs that are available for use. A noncommercial capillary type plunger was also tested with two sizes of orifices, resulting in the evaluation of a total of thirteen plunger configurations. General types of plungers tested included capillary, turbulent seal brush, expandable blade, multiple turbulent seal, multiple expandable blade, combination turbulent seal and expandable blade, and wobble washer. Valving arrangements through the plungers included full opening, internal valve stem, and solid plug. Table I lists the types of plungers tested, together with a brief description and identifier number.

TABLE I  
Plunger Description

| Plunger<br>Number | Type                 | Valve Arrangement   | Weight<br>lbs | Threshold<br>SCFM | Lift<br>PSIG |
|-------------------|----------------------|---------------------|---------------|-------------------|--------------|
| 1,21              | Capillary            | None                | 5.125         | 48.8              |              |
| 2                 | Turbulent Seal       | None                | 7.375         | 51.4              | 2.44         |
| 3                 | Brush                | Integral Valve Rod  | 5.4375        | 34.1              | 1.82         |
| 4                 | Brush                | Lubricator Actuated | 6.75          | 22.6              | 2.20         |
| 5                 | Dual Turbulent Seal  | Integral Valve Rod  | 10.0          | 32.1              | 3.28         |
| 6                 | Turbulent-Expanding  | Integral Valve Rod  | 10.125        | 23.4              | 3.43         |
| 7                 | Dual Expanding Blade | Integral Valve Rod  | 10.75         | 22.7              | 3.50         |
| 8                 | Expanding Blade      | None                | 5.375         | 32.1              | 2.09         |
| 9                 | Dual Expanding Blade | Integral Valve Rod  | 8.25          | 28.2              | 3.32         |
| 10                | Sgl. Expanding Blade | Integral Valve Rod  | 6.1875        | 41.5              | 2.35         |
| 11                | Wobble Washer        | Integral Valve Rod  | 10.375        | 29.3              | 3.39         |
| 12                | Dual Expanding Blade | Lubricator Actuated | 10.25         | 21.9              | 3.25         |

### TEST PROGRAM AND PROCEDURES

The threshold lift characteristics (see Table I) of each plunger were measured at the surface using a 1.990 in. ID lucite tube. Air flowing into the bottom of the tube was gradually adjusted to the rate at which the plunger would be suspended in the flow stream. The corresponding flow rate in SCFM and the pressure under the plunger are listed in Table I. In most cases, the threshold lift pressure simply equals the weight of the plunger divided by the cross sectional area of the tubing. Notable exceptions are Plungers 8, 9 and 10, for which no explanation is apparent other than possibly friction loss past the plungers.

Plunger performance was evaluated with slug sizes of 5 and 10 gallons of water. Water was pumped out of the separator and metered upstream of the wellhead. Pressure on the lower transducer was monitored to determine when the liquid slug arrived on bottom. Since a check valve was in place, pressure on the bottom transducer would increase over the casing pressure by an amount corresponding to the hydrostatic head of the liquid slug. Tubing pressure was then bled off until the pressure in the bottom of the tubing was in balance with casing pressure.

When this hydrostatic balance was achieved, the plunger was dropped and the pressure response on the tubing transducers recorded. After the plunger reached bottom and pressure response stabilized, the tubing valve on the surface was opened to start the rise cycle and initiate data collection. The valve was closed immediately on plunger arrival, but data collection was continued to reflect stable casing pressure and indicate liquid fallback.

#### EXPERIMENTAL RESULTS

A typical pressure history during fall is shown on Figure 2. A slight increase in downhole tubing pressure was noted as the plunger fell. A sharp decrease in tubing pressure was seen as the plunger passed each transducer above the liquid level. It is interesting to note that the change in pressure during plunger passage is nearly equal to the expected threshold lift pressure for plungers 8, 9, and 10. These pressure changes as a function of time were used to calculate fall velocity in air and to predict plunger arrival at the top of the liquid slug. In most cases, a similar sharp drop in pressure was noted at the bottom transducer as the plunger stopped on the shock absorber at the check valve. This permitted the calculation of fall velocity in water. Fall velocities in air collected in the lab as a function of pressure were not sufficient to extrapolate to high pressure field conditions. The fall velocities in water for plungers 1-12 are: 1.22, .95, 1.86, 3.07, 1.43, 1.1, 1.21, .656, 1.536, 2.45, 7.45 and 3.94 fps.

Typical rise cycle pressure response is shown in Figures 3-6, representing a series of plunger runs with slug size of approximately 10 gallons of water and with initial casing pressure sequentially decreased from 80 psig to 30 psig or stall-out pressure. Pressure response during the plunger rise period is shown by six curves. Pressure changes recorded by the bottom transducer and the casing transducer reflect the decrease in lift gas pressure (and volume). The remaining four present time-and-pressure related events during plunger rise. Beginning from the left hand side of the chart, it may be observed that these transducers respond in similar fashion to a very rapid decline in tubing pressure above the liquid slug. The first upward inflection indicates the top of the liquid slug passing the transducer located at 536 feet or approximately 179 feet off bottom. By knowing the size of the liquid slug and its height above bottom, the average velocity and acceleration may be determined by the lapsed time to this point.

Pressure increases abruptly as the liquid slug continues to rise above the transducer with pressure reaching a plateau as the plunger passes. A slight increase in pressure may also be noted as the liquid slug reaches the surface and passes through several bends and fittings before reaching the separator.

At higher casing pressure, plunger velocity is high, gas slippage is low and a uniform fluid gradient is exhibited as the liquid slug passes the transducer. Tests run with lower casing pressure result in lower plunger velocity and longer plunger arrival time. The lower velocity permits increased gas slippage past the plunger, which is shown by an irregular liquid gradient during traverse past the transducer. This is seen as an elongating gas cut liquid slug. At stall-out, the plunger ceases to move upward, and liquid removal is effected by gas lift with the plunger acting essentially as a downhole restriction. Pressure buildup on the bottom transducer after plunger arrival is a function of liquid fallback or penetration of the liquid slug during high velocity rise of the plunger. Figure 7 presents a least squares fit of fallback in gallons per second vs plunger velocity. Note that fallback is depicted as being zero at low velocities but if the period of measurement was extended, some liquid from the tubing walls would have probably been measured at all velocities.

Figure 8 depicts the pressure history with no plunger in the well. Even though the initial casing pressure was 70 psig, the pressure behavior looks more like Figure 6, where stall-out occurred with a plunger at 30 psig casing pressure.

Total gas slippage from below to above the plunger for each run was also measured. A typical plot of gas slip in scf versus plunger average velocity is shown in Figure 9. The physics gas slip are analyzed in more detail in following discussion.

A summary of data from 132 valid tests processed is shown in Appendix A. These data provide the basis for characterizing gas slip and liquid fallback.

## FIELD TESTING

Field testing was conducted with multiple tests at four wells in three fields in conjunction with Camco, Inc. and Ferguson-Beauregard, Inc. The purpose of the field tests was to obtain field data of sufficient quality to provide a basis for comparison with laboratory data. The expected end result was to be a mathematical model incorporating adjusted laboratory developed plunger correlations which would improve plunger selection and operation. Field pressure measurements were made with Rosemount transducers tied in to a Hewlett Packard 9826 computer. In those fields having automation systems, existing transducers were used. Measurement was made of casing pressure, tubing pressure, and orifice meter static and differential pressure as a function of time during plunger cycles. Liquid volumes were made by tank gauging or by sight glass measurement where temporary tanks permitted. Pressure measurement sampling frequency was at 0.1 second intervals during critical periods and at longer

intervals during non critical periods. Operating conditions such as cycle time and back pressure were adjusted where possible to produce as many types of operating conditions as possible. Figure 10 shows an overall view of a typical instrumental well site.

The initial test was conducted near Pampa, Texas. The well is approximately 10,000 ft deep, cased with 7 in. and dually completed with two strings of 2-3/8 in. tubing. Normal average daily production prior to the test was reported as 800 MCFD, 39.6 Bbl condensate, and 5.8 Bbl water.

The next well tested was a relatively low volume producer completed in the Travis Peak Formation in the Carthage Field in East Texas. Typical oil producing rate was 6 BOPD. The well was scheduled to shut in on plunger arrival with a 3.5 hour shut in for a cycle frequency of 6 cycles per day.

The third well tested was also in the Carthage field lifting small slugs on a frequency of about 10 cycles per day, produced 3-4 barrels per day. Normal operation was to continue afterflow following plunger arrival and shut in on low tubing pressure of about 250 psi.

The final well tested was near Dacona, Colorado. This well had low pressure and relatively small lift volume storage since it was equipped with 4-1/2 ft casing and 2 in. tubing to 5039 ft. Both the normal wobble washer plunger and an expanding seal plunger were run in this series of tests. This well was interesting because of its slow plunger travel and its tendency to stall. When the plunger stalled, it was necessary to equalize tubing and casing pressure at the surface and then shut in before initiating plunger rise. Figure 11 shows a normal but slow lift cycle while Figure 12 is representative of pressure behavior during stall, equalization of casing and tubing surface pressures, and lift.

#### ANALYSIS OF LABORATORY AND FIELD DATA

##### Previous Analytical Work:

There have been several previous publications in the area of plunger lift operations (see References 1-8).

Of those cited, the analysis by Foss and Gaul<sup>2</sup> is probably used the most frequently because it is simple and considers most of the necessary physics of the operation. This method is outlined in detail in the following discussion.

##### Modification of Foss & Gaul<sup>2</sup> Theoretical Model to Fit Data Collected

Foss and Gaul<sup>2</sup> have presented a method for analyzing and designing pressure requirements for plunger lift.

The following formula for maximum and minimum casing pressure during a plunger cycle summarizes much of their theoretical work.

$$P_{\max} = P_{\min} \text{ CPR} \quad (1)$$

where:  $\text{CPR} = \frac{A_a + A_t}{A_a}$

$A_a$  = cross-sectional area of annulus  
 $A_t$  = cross-sectional area of tubing  
 $P_{\max}$  = casing pressure just before tubing is opened, psia  
 and cycle begins  
 $P_{\min}$  = casing pressure just as slug arrives at surface, psia

$$P_{\min} = \langle PP + 14.7 + P_t + (P_{LH} + P_{LF})XL \rangle * \langle 1 + \frac{\text{Depth}}{K} \rangle \quad (2)$$

where:  $PP$  = pressure to lift plunger weight, psi  
 $P_t$  = tubing pressure, psig  
 $P_{LF}$  = pressure to overcome liquid friction, psi/bbl  
 $P_{LH}$  = pressure to lift liquid weight, psi/bbl  
 $XL$  = barrels of liquid in the slug  
 $\text{Depth}$  = well depth, feet  
 $K$  = term for gas friction in tubing

The particular expressions for the components of  $P_{\min}$  are:

$$P_{LH} = \text{SPG} * G_w * L \quad (3)$$

where:  $\text{SPG}$  = the specific gravity of fluid to be lifted  
 $L$  = the length of one barrel of liquid in the tubing  
 $G_w$  = .433 psi/ft (fresh water gradient)

$$P_{LF} = \frac{SPG \times .433 \times f_{\text{slug}} \times L \times V^2}{D/12 \times 2.0 \times 32.2} \quad (4)$$

where:  $f_{\text{slug}}$  = a Darcy Weisbach friction factor for the liquid slug  
 $V$  = velocity in fps  
 $D$  = tubing diameter, in.

$$\frac{1}{K} = \frac{f_g \times V^2 \times G_g}{D/12 \times 2 \times 32.2 \times (T + 460) \times Z \times R} \quad (5)$$

where:  $f_g$  = a Darcy Weisbach friction factor for gas flow through the tubing

$G_g$  = gas gravity

$R$  = gas law constant, 53.3 lbf-ft/(°R-lbm)

$T$  = temperature, °F

$Z$  = gas compressibility factor, dim'less

The  $P_{\min}$  described in the above equations is the pressure in the casing as the slug and plunger just reach the surface. The  $P_{\max}$  is the level the casing pressure must reach before the slug and plunger are allowed to begin to surface after a normally required well shut-in period. The  $P_{\max}$  is a function of the velocity of rise which can be selected as a function of measured plunger characteristics. In the above form, no gas is assumed to produce into the well during the rise of the plunger and the liquid.

If gas production from the formation during plunger rise is accounted for, then the maximum ( $P_{\max}$ ) pressure requirement is reduced, but the minimum ( $P_{\min}$ ) requirement remains the same.

Also, if gas is lost from below the plunger to above it during rise (gas slip-page), the requirement for  $P_{\max}$  will increase, but the  $P_{\min}$  requirement remains constant.

The following illustrates the functional dependence of  $P_{\max}$  on slip and well production.



$$P_{\max} = P_{\min} \text{ CPR} - \frac{(\text{PRGAS} - \text{SLIP})(14.7)(T + 460)}{V_c 520} \quad (6)$$

where:  $V_c$  = volume of casing,  $\text{ft}^3$

SLIP = gas slippage past the plunger (which was measured during laboratory tests in SCF)

PRGAS = gas produced into well during the time period that the plunger rises, SCF

For laboratory test conditions, PRGAS was zero. The slip was measured, and can be calculated from the correlation developed in Appendix B and plotted in Figure 13. Note that the slip is used to increase the required  $P_{\max}$  because casing shut-in pressure must be larger than normal so that, as expansion and slip occur, the  $P_{\min}$  requirement is met at the surface.

Another effect which tends to reduce pressure requirements is liquid fallback. As shown in Figure 7, liquid fallback increases as the velocity increases but at different rates for different plungers. Since the  $P_{\min}$  is calculated as a function of the slug size at the surface, the  $P_{\min}$  based on a starting bottom-hole slug size is reduced by the amount of liquid fallback as the plunger rises. A  $P_{\min}$  based on surface measured production is unaffected. However, operation at high velocities is to be avoided to prevent large liquid losses from above the plunger.

#### Adjustment of Laboratory Correlations to Match Field Data

The method of Foss & Gaul<sup>2</sup> is to consider a force balance on the liquid slug and plunger as it surfaces. The expressions for the casing pressure requirements are outlined in Eqs. (1) through (6).

When comparing field data to the model developed from Foss and Gaul and laboratory correlations, a plot of actual casing minimum pressure,  $P_{c\min}$ , versus  $P_{c\min}$  from calculations was made. From Figure 14, it can be seen that the adjusted Foss & Gaul underpredicts for low slugs (low pressures) and overpredicts for large slugs (large pressures). Therefore, the following purely empirical adjustment was made to the Foss & Gaul model to fit the field data more closely.

$$P_{c,min} = -9.9242 + 1.67722 * P_{minlab} - 0.0008643 * P_{minlab}^2$$

This adjustment resulted in an expression which fit the field data within -1% average error with 9.4 standard deviation of actual compared to calculated  $P_{c,min}$ . This adjustment may have been due to larger amounts of gas being lost as slip in the laboratory when the plunger is accelerated compared to the total lost over long lengths of tubing. The loss when accelerating in field conditions would be a lesser percent of the whole.

### Model for Plunger Lift Cycles

A typical cycle for a plunger lifted well is to shut the well in and allow the casing pressure to build to a required maximum. The tubing is then opened and the slug and plunger rise to the surface. If the gas/liquid ratio of the well is high enough, then the plunger can be held at the surface to allow additional gas production before the well is shut-in again and the plunger is allowed to fall.

For many "tight" gas wells (low permeability), a plot of bottomhole pressure versus production is very steep indicating that production does not change much if the BHP is changed. If a plunger lift well is assumed to produce at a constant rate regardless of pressure, then the shut-in and producing times for a cycle can be calculated.

The casing pressure must build to  $P_{max}$  casing pressure (Eq. (6)). If the well is allowed to blow down to a pressure  $P_{low}$  with the plunger at the surface, the buildup time required  $t_{bu}$  can be found from:

$$t_{bu} \text{ (minutes)} = \text{mass}/\text{mrate} \quad (7)$$

where: mass = change in mass of gas in the casing plus tubing  
as the pressure changes from  $P_{low}$  to  $P_{max}$   
lbm  
mrate = (rate, MCFD)( $\rho_{g \text{ s.c.}}$ )1000/(24)(60), lbm/min  
rate = input approximate rate of gas production from  
well, MCFD  
 $\rho_{g \text{ s.c.}}$  = density of gas at standard conditions, lbm/ft<sup>3</sup>

All of the above quantities can be calculated using appropriate gas law expressions.

Note that for a given slug size delivered, the time can be calculated for complete cycle,  $t_{\text{cycle}}$ .

$$t_{\text{cycle}} = \left( \frac{\text{slug size, bbls}}{\text{rate, MCFD}} \right) \left( \text{GLR, } \frac{\text{SCF}}{\text{bbl}} \right) \frac{(24)(60)}{(1000)}, \text{ minutes} \quad (8)$$

The difference between the cycle time,  $t_{\text{cycle}}$ , and the buildup time,  $t_{\text{bu}}$ , is the production time,  $t_{\text{prod}}$ , while the tubing is open to flow.

$$t_{\text{prod}} = t_{\text{cycle}} - t_{\text{bu}} \text{ for } t_{\text{cycle}} \geq t_{\text{bu}} \quad (9)$$

$$t_{\text{prod}} = 0 \quad \text{for } t_{\text{bu}} > t_{\text{cycle}}$$

Note that if  $t_{\text{bu}} > t_{\text{cycle}}$ , then the required buildup time is greater than the total cycle time,  $t_{\text{cycle}}$ , and  $t_{\text{prod}}$  is zero. For  $t_{\text{bu}} > t_{\text{cycle}}$ , production is not possible, for the given slug size, for continuing similar cycles.

There are other restrictions on a plunger lift cycle. If the  $P_{\text{max}}$  (Eq. (6)) is calculated to be higher than the well shut-in pressure, then production is not possible.

Also if the well gas/liquid ratio is too low, then production is not possible. The minimum gas liquid ratio required must be at least equal to gas in the tubing at  $P_{\text{min}}$  before production is possible. Once production is possible, the well GLR must exceed the gas produced during a cycle divided by the liquid produced for a cycle. In addition, the time to rise must be included in this buildup time, or alternatively the producing times must exceed the time to rise.

The remaining variable to be calculated is the time for the well to blow down from the  $P_{\text{min}}$  casing pressure to a low limit  $P_{\text{low}}$  casing pressure. Since wells have a variety of surface hardware and line sizes, this is assumed to be in the same proportion as the time required for the casing pressure to change from  $P_{\text{max}}$  to  $P_{\text{min}}$  as the plunger rises. This assumption fits field collected data fairly well.

An example output is as shown in Figure 15. On the left is a series of slug sizes. The well is shown to be unable to produce continuously below a slug size of 0.85 bbls because the well GLR is too low. These results are, of course, for the particular well input data shown at the top of Figure 15. Also note that the well cannot continuously produce a slug size of greater than

2.85 bbls because the buildup pressure required then exceeds the well input shut-in pressure. This example was generated with a rise velocity in the program of 1000 fpm but other values could be input which might better suit the slip and liquid fallback characteristics of each plunger tested in the lab and field tests. For analysis purposes, a program allowing the input of actual velocity could be used to compare program predicted operation to actual operation.

Again this type of analysis is dependent on assuming constant well gas production over the range of pressures needed for a complete cycle. If the well in question does not fit the assumption of a "tight" gas well, then the cycle times calculated would be in error. However the shut-in pressure required for the wells should still be calculated using realistic assumptions.

#### BIBLIOGRAPHY

1. Lebeaux, J. M. and Sudduth, L. F., "Theoretical and Practical Aspects of Free Piston Operation," JPT, September, 1955, pp. 33-35.
2. Foss, D. L. and Gaul, R. B., "Plunger-Lift Performance Criteria with Operating Experience--Ventura Avenue Field," Drilling and Production Practice, API, 1965, pp. 124-140.
3. Hacksma, J. D., "Users Guide to Predicting Plunger Lift Performance," Presented at Southwestern Petroleum Short Course, Lubbock, Texas, 1972.
4. Abercrombie, B., "Plunger Lift," published in The Technology of Artificial Lift Methods, Vol. 26, by K. E. Brown, 1980, Pet. Pub. Co.
5. Beauregard, E. M. and Ferguson, P. L., Petroleum Engineer International, July, 1981.
6. Lea, J. F., "Dynamic Analysis of Plunger Lift Operations," JPT, November 1982, pp. 2617-2630.
7. Phenicie, T. H. and Williams, B. J., Amoco Report "Hugoton and Panoma Council Grove Plunger Lift Review," dated November 30, 1981.
8. Beeson, C. M., Knox D. G. and Stoddard, J. H., "The Plunger Lift Method of Oil Production," Paper 501-G presented at AIME Petroleum Branch, New Orleans, October 1975.

## ACKNOWLEDGMENTS

The authors would like to thank Amoco for permission to publish the paper. Also, credit must be given to Camco and Ferguson-Beauregard, Inc., for supplying field data gathering instrumentation and also plunger lift hardware for test. Walter Goins and Herb Maier with Camco instrumented the wells and collected data on computer systems at the well sites, and Paul Ferguson and Earnest Beauregard provided various types of plungers and provided assistance with the controllers, instrumentation, data taking, etc. Also, Amoco field personnel from the Montbello, Colorado, Pampa, Texas, and Carthage, Texas, offices arranged tests at the individual wells and provided support during the tests. Special thanks are due Don Curnutt for design and development of the downhole transducer system and to Steve Andrews and Robert Joha for their assistance in data collection and processing.

## APPENDIX A

Table 1 summarizes the test results and the comparisons to the Foss and Gaul<sup>2</sup> model corrected for gas bypass and liquid fallback. The columns "CALSLP" and "ACTSLP" just compare actual data to data from correlations or curve fits developed. The "VEL, FPM" column is the actual measured average velocity of rise. The "ACTUAL CSG P" column is the actual casing pressure measured and the " $P_{max}$ " is the pressure calculated from the corrected Foss and Gaul equations.

The error column is the percent error between the measured casing pressure and the calculated  $P_{max}$ . The column "FALBK" is measured liquid fallback in gallons.

At the end of the table are summaries of average errors for the whole series of tests. Note that the average absolute error for the minimum pressure compared to data is 5.92% (minimum pressures not tabulated) and the average absolute error for the  $P_{max}$  compared to data is 7.03%. Summing errors with the plus or minus considered give 2.7% error, and the standard deviation of the absolute errors for  $P_{max}$  is 8.8%.

The average error of 7% for  $P_{max}$  compared to the data is probably close to the accuracy of some of the data collected, such as liquid fallback with small slug sizes.

Table 1  
Tabulated Results from Laboratory Tests

| PLUNGER<br>NUMBER | CALSLP<br>SCF | ACTSLP<br>SCF | VEL<br>FPM | ACTUAL<br>CSG P | PMAX<br>F + G | ERROR  | FALBK |
|-------------------|---------------|---------------|------------|-----------------|---------------|--------|-------|
| 1                 | 160.172       | 170.760       | 303.620    | 29.440          | 29.351        | 0.303  | 0.0   |
| 1                 | 53.460        | 46.580        | 859.260    | 39.450          | 33.639        | 14.730 | 0.0   |
| 1                 | 36.309        | 32.150        | 1197.540   | 49.560          | 42.749        | 13.743 | 0.210 |
| 1                 | 26.684        | 25.850        | 1504.090   | 59.320          | 48.849        | 17.652 | 0.630 |
| 1                 | 18.583        | 20.330        | 1860.970   | 69.280          | 62.741        | 9.438  | 0.920 |
| 1                 | 17.127        | 19.200        | 1976.610   | 79.680          | 64.019        | 19.655 | 1.250 |
| 2                 | 132.307       | 135.970       | 336.600    | 29.240          | 29.178        | 0.212  | 0.0   |
| 2                 | 50.242        | 45.910        | 847.670    | 39.160          | 34.694        | 11.403 | 0.0   |
| 2                 | 36.787        | 34.550        | 1130.050   | 49.120          | 41.359        | 15.800 | 0.070 |
| 2                 | 21.315        | 20.480        | 1643.710   | 58.880          | 51.775        | 12.067 | 0.760 |
| 2                 | 17.685        | 16.790        | 1862.990   | 68.940          | 64.129        | 6.978  | 0.690 |
| 2                 | 14.523        | 18.540        | 2082.030   | 79.390          | 74.135        | 6.619  | 0.740 |
| 3                 | 51.933        | 57.960        | 416.370    | 24.800          | 23.644        | 4.661  | 0.0   |
| 3                 | 38.733        | 41.970        | 577.370    | 29.880          | 27.745        | 7.145  | 0.0   |
| 3                 | 17.907        | 15.210        | 1205.100   | 39.690          | 38.786        | 2.277  | 0.680 |
| 3                 | 10.799        | 10.040        | 1834.470   | 49.310          | 46.534        | 5.629  | 0.940 |
| 3                 | 10.525        | 9.430         | 1953.390   | 59.220          | 59.988        | -1.296 | 1.210 |
| 3                 | 11.267        | 13.620        | 1946.750   | 69.180          | 64.807        | 6.321  | 1.070 |
| 4                 | 12.955        | 15.600        | 659.540    | 24.410          | 25.558        | -4.703 | 0.0   |
| 4                 | 10.677        | 10.500        | 939.470    | 29.290          | 30.670        | -4.713 | 0.220 |
| 4                 | 9.227         | 7.590         | 1394.970   | 39.550          | 41.440        | -4.778 | 0.640 |
| 4                 | 8.980         | 6.670         | 1705.170   | 49.750          | 52.242        | -5.009 | 0.900 |
| 4                 | 9.101         | 7.430         | 1893.800   | 59.270          | 60.064        | -1.340 | 1.230 |
| 4                 | 9.534         | 12.140        | 1964.560   | 69.670          | 67.030        | 3.789  | 1.270 |
| 4                 | 9.372         | 10.300        | 2265.070   | 78.900          | 76.276        | 3.326  | 1.380 |
| 5                 | 98.217        | 91.400        | 452.020    | 30.020          | 27.493        | 8.418  | 0.0   |
| 5                 | 59.780        | 55.430        | 809.330    | 39.350          | 33.193        | 15.646 | 0.0   |
| 5                 | 49.039        | 46.880        | 1061.380   | 49.410          | 41.528        | 15.952 | 0.0   |
| 5                 | 38.171        | 37.470        | 1434.580   | 59.370          | 49.169        | 17.181 | 0.0   |
| 5                 | 34.798        | 37.060        | 1651.080   | 69.090          | 63.167        | 8.572  | 0.060 |
| 5                 | 34.550        | 34.290        | 1750.350   | 79.190          | 73.072        | 7.726  | 0.140 |
| 6                 | 79.320        | 91.220        | 291.640    | 24.600          | 24.698        | -0.400 | 0.0   |
| 6                 | 33.042        | 32.560        | 664.130    | 29.590          | 27.239        | 7.944  | 0.0   |
| 6                 | 14.701        | 9.330         | 1275.500   | 39.740          | 41.352        | -4.055 | 0.350 |
| 6                 | 11.338        | 8.970         | 1548.850   | 49.410          | 49.754        | -0.695 | 0.740 |
| 6                 | 10.883        | 9.220         | 1641.620   | 59.420          | 56.249        | 5.336  | 0.850 |
| 6                 | 7.598         | 8.250         | 1982.700   | 69.670          | 65.976        | 5.303  | 1.030 |
| 6                 | 6.458         | 9.840         | 2147.100   | 79.340          | 77.485        | 2.338  | 1.230 |
| 7                 | 37.018        | 37.880        | 629.110    | 29.150          | 27.000        | 7.374  | 0.0   |
| 7                 | 23.528        | 18.540        | 1023.640   | 39.300          | 34.634        | 11.873 | 0.0   |
| 7                 | 17.423        | 11.530        | 1398.000   | 49.750          | 49.391        | 0.721  | 0.0   |
| 7                 | 16.710        | 18.480        | 1516.040   | 58.930          | 59.878        | -1.609 | 0.010 |

Table 1 (cont'd)  
Tabulated Results from Laboratory Tests

| PLUNGER<br>NUMBER | CALSLP<br>SCF | ACTSLP<br>SCF | VEL<br>FPM | ACTUAL<br>CSG P | PMAX<br>F + G | ERROR   | FALBK |
|-------------------|---------------|---------------|------------|-----------------|---------------|---------|-------|
| 7                 | 13.890        | 15.770        | 1814.440   | 68.990          | 66.506        | 3.600   | 0.420 |
| 7                 | 10.449        | 10.900        | 2259.110   | 77.390          | 61.731        | 20.233  | 0.780 |
| 8                 | 48.043        | 49.670        | 502.780    | 24.360          | 23.542        | 3.357   | 0.0   |
| 8                 | 32.034        | 31.640        | 784.680    | 29.540          | 27.183        | 7.979   | 0.020 |
| 8                 | 21.901        | 19.050        | 1219.650   | 39.740          | 39.029        | 1.788   | 0.040 |
| 8                 | 17.627        | 15.620        | 1581.650   | 49.560          | 52.009        | -4.942  | 0.080 |
| 8                 | 17.210        | 16.900        | 1714.250   | 59.520          | 60.245        | -1.218  | 0.060 |
| 8                 | 16.248        | 16.190        | 1893.800   | 69.530          | 71.318        | -2.571  | 0.280 |
| 8                 | 15.004        | 15.720        | 2110.170   | 79.290          | 80.508        | -1.536  | 0.390 |
| 9                 | 62.884        | 64.360        | 351.000    | 24.260          | 23.849        | 1.694   | 0.0   |
| 9                 | 35.816        | 34.960        | 650.140    | 29.150          | 26.935        | 7.600   | 0.0   |
| 9                 | 24.183        | 23.700        | 1046.510   | 39.010          | 37.194        | 4.655   | 0.0   |
| 9                 | 20.408        | 20.070        | 1330.500   | 49.020          | 46.731        | 4.669   | 0.0   |
| 9                 | 17.578        | 16.950        | 1637.960   | 59.470          | 57.176        | 3.857   | 0.0   |
| 9                 | 15.037        | 15.520        | 1994.210   | 69.230          | 70.367        | -1.642  | 0.200 |
| 9                 | 16.206        | 15.510        | 1955.610   | 78.560          | 79.524        | -1.227  | 0.270 |
| 10                | 106.235       | 104.140       | 420.890    | 29.000          | 28.114        | 3.055   | 0.0   |
| 10                | 45.431        | 43.300        | 986.980    | 39.790          | 32.219        | 19.028  | 0.030 |
| 10                | 40.217        | 38.030        | 1161.900   | 49.510          | 39.284        | 20.654  | 0.0   |
| 10                | 30.558        | 25.850        | 1504.090   | 59.320          | 52.088        | 12.192  | 0.620 |
| 10                | 25.851        | 27.030        | 1760.510   | 69.380          | 59.688        | 13.969  | 0.320 |
| 10                | 24.574        | 27.180        | 1886.870   | 79.490          | 74.149        | 6.719   | 0.410 |
| 11                | 47.608        | 47.420        | 489.500    | 24.650          | 24.728        | -0.315  | 0.0   |
| 11                | 37.672        | 34.450        | 663.110    | 29.630          | 27.219        | 8.136   | 0.0   |
| 11                | 29.156        | 26.310        | 956.030    | 39.300          | 34.797        | 11.459  | 0.0   |
| 11                | 23.323        | 23.400        | 1317.230   | 49.560          | 43.856        | 11.508  | 0.0   |
| 11                | 21.939        | 22.580        | 1514.700   | 59.660          | 54.281        | 9.016   | 0.0   |
| 11                | 21.223        | 21.710        | 1667.110   | 68.890          | 63.405        | 7.962   | 0.010 |
| 11                | 19.539        | 17.720        | 1933.600   | 79.240          | 73.383        | 7.391   | 0.230 |
| 12                | 25.036        | 28.870        | 594.900    | 29.390          | 29.480        | -0.306  | 0.0   |
| 12                | 13.864        | 8.760         | 1288.260   | 39.350          | 41.200        | -4.701  | 0.0   |
| 12                | 14.536        | 10.860        | 1346.490   | 49.460          | 49.464        | -0.008  | 0.130 |
| 12                | 12.774        | 10.200        | 1707.990   | 59.420          | 65.600        | -10.401 | 0.0   |
| 12                | 11.942        | 10.040        | 2008.980   | 69.820          | 67.543        | 3.261   | 0.720 |
| 12                | 11.828        | 14.440        | 2175.190   | 79.590          | 84.047        | -5.600  | 0.790 |
| 21                | 74.569        | 73.440        | 529.110    | 29.540          | 26.970        | 8.700   | 0.0   |
| 21                | 38.293        | 32.760        | 969.890    | 39.640          | 34.086        | 14.012  | 0.0   |
| 21                | 21.288        | 18.440        | 1479.060   | 49.650          | 47.662        | 4.004   | 0.450 |
| 21                | 17.424        | 16.640        | 1700.670   | 59.760          | 57.589        | 3.633   | 0.760 |
| 21                | 14.397        | 15.060        | 1903.600   | 69.670          | 66.615        | 4.385   | 0.870 |
| 21                | 14.251        | 17.720        | 1953.390   | 79.240          | 73.676        | 7.022   | 0.810 |
| 1                 | 242.496       | 261.330       | 224.930    | 39.550          | -43.010       | -8.748  | 0.0   |

Table 1 (cont'd)  
Tabulated Results from Laboratory Tests

| PLUNGER<br>NUMBER | GALSLP<br>SCF | ACTSLP<br>SCF | VEL<br>FPM | ACTUAL<br>CSG P | PMAX<br>F + G | ERROR   | FALBK |
|-------------------|---------------|---------------|------------|-----------------|---------------|---------|-------|
| 1                 | 61.541        | 56.560        | 871.770    | 59.710          | 54.538        | 8.662   | 0.010 |
| 1                 | 31.066        | 32.450        | 1519.620   | 89.350          | 86.820        | 2.832   | 0.410 |
| 2                 | 205.347       | 230.270       | 243.900    | 39.500          | 43.947        | -11.257 | 0.0   |
| 2                 | 48.090        | 41.050        | 988.870    | 59.660          | 57.672        | 3.332   | 0.030 |
| 2                 | 26.455        | 27.690        | 1606.310   | 89.250          | 89.058        | 0.215   | 0.510 |
| 3                 | 45.808        | 51.390        | 542.310    | 39.500          | 36.692        | 7.109   | 0.0   |
| 3                 | 21.100        | 19.770        | 1197.540   | 59.570          | 61.445        | -3.148  | 0.320 |
| 3                 | 14.516        | 16.950        | 1771.410   | 89.300          | 93.912        | -5.164  | 0.740 |
| 4                 | 14.132        | 16.540        | 730.510    | 39.350          | 41.673        | -5.902  | 0.020 |
| 4                 | 10.859        | 8.150         | 1381.510   | 59.520          | 70.762        | -18.887 | 0.660 |
| 4                 | 10.995        | 13.930        | 1827.310   | 89.400          | 100.212       | -12.094 | 1.300 |
| 5                 | 188.386       | 213.640       | 255.980    | 39.600          | 41.590        | -5.024  | 0.0   |
| 5                 | 66.748        | 64.380        | 849.770    | 59.660          | 53.093        | 11.008  | 0.0   |
| 5                 | 47.177        | 49.700        | 1382.620   | 89.600          | 85.455        | 4.626   | 0.040 |
| 6                 | 58.526        | 64.790        | 447.420    | 39.690          | 37.943        | 4.401   | 0.0   |
| 6                 | 17.734        | 12.960        | 1250.430   | 59.570          | 63.038        | -5.822  | 0.100 |
| 6                 | 10.653        | 13.880        | 1797.360   | 89.450          | 99.607        | -11.354 | 0.760 |
| 7                 | 74.224        | 79.580        | 363.370    | 39.500          | 39.921        | -1.067  | 0.0   |
| 7                 | 42.406        | 43.560        | 659.040    | 48.870          | 47.157        | 3.505   | 0.0   |
| 7                 | 30.603        | 32.400        | 937.940    | 59.570          | 57.896        | 2.811   | 0.0   |
| 7                 | 24.997        | 26.980        | 1167.690   | 69.430          | 67.782        | 2.373   | 0.0   |
| 7                 | 20.954        | 21.190        | 1398.380   | 78.710          | 77.343        | 1.737   | 0.110 |
| 7                 | 19.411        | 19.610        | 1544.210   | 89.550          | 69.345        | 22.563  | 0.110 |
| 8                 | 47.777        | 50.310        | 593.180    | 39.600          | 37.192        | 6.082   | 0.040 |
| 8                 | 27.024        | 26.570        | 1161.900   | 59.570          | 58.872        | 1.171   | 0.0   |
| 8                 | 21.329        | 26.420        | 1651.080   | 89.550          | 99.141        | -10.710 | 0.020 |
| 8                 | 21.329        | 26.420        | 1651.080   | 89.550          | 99.805        | -11.451 | 0.100 |
| 9                 | 59.292        | 60.140        | 440.050    | 39.500          | 38.764        | 1.864   | 0.0   |
| 9                 | 29.545        | 29.640        | 1009.010   | 59.420          | 59.812        | -0.660  | 0.0   |
| 9                 | 20.633        | 22.880        | 1650.550   | 89.200          | 100.131       | -12.255 | 0.0   |
| 10                | 226.831       | 241.940       | 222.210    | 39.500          | 43.523        | -10.186 | 0.0   |
| 10                | 71.826        | 71.390        | 765.790    | 59.470          | 51.060        | 14.142  | 0.050 |
| 10                | 45.235        | 48.670        | 1279.620   | 89.640          | 80.177        | 10.557  | 0.180 |
| 11                | 64.101        | 67.970        | 425.510    | 39.450          | 39.262        | 0.478   | 0.0   |
| 11                | 33.009        | 33.220        | 992.680    | 59.710          | 60.104        | -0.660  | 0.0   |
| 11                | 26.240        | 29.640        | 1497.100   | 89.250          | 94.630        | -6.028  | 0.0   |
| 12                | 27.722        | 32.920        | 596.140    | 39.500          | 38.596        | 2.288   | 0.0   |
| 12                | 23.554        | 27.290        | 781.350    | 49.560          | 49.629        | -0.140  | 0.0   |
| 12                | 17.264        | 15.770        | 1202.010   | 59.660          | 64.850        | -8.699  | 0.0   |
| 12                | 15.670        | 15.110        | 1446.260   | 69.620          | 78.363        | -12.559 | 0.280 |
| 12                | 14.754        | 14.600        | 1657.990   | 79.440          | 89.333        | -12.453 | 0.610 |
| 12                | 14.376        | 16.690        | 1818.930   | 89.550          | 99.301        | -10.889 | 0.590 |



Table 1 (cont'd)  
Tabulated Results from Laboratory Tests

| PLUNGER<br>NUMBER | CALSLP<br>SCF | ACTSLP<br>SCF | VEL<br>FPM | ACTUAL<br>CSG P | PMAX<br>F + G | ERROR   | FALBK |
|-------------------|---------------|---------------|------------|-----------------|---------------|---------|-------|
| 12                | 14.306        | 16.390        | 1931.420   | 99.170          | 120.240       | -21.247 | 0.700 |
| 12                | 14.534        | 16.590        | 1892.410   | 98.970          | 110.407       | -11.556 | 0.700 |
| 21                | 46.940        | 41.260        | 937.940    | 59.470          | 55.593        | 6.520   | 0.0   |
| 21                | 27.492        | 29.590        | 1466.430   | 89.300          | 86.441        | 3.202   | 0.410 |

AVG PCT ERROR(FOSS)= 7.03

AVG PCT ERROR(MIN PRESS)= 5.92

AVG ERR WITH SIGN FOR FOSS 2.71

STANDARD DEVIATION = 8.853

## APPENDIX B

### Correlation Parameter for Experimental Data for Gas Slippage Past a Plunger

If the data is examined from the tests performed in the test well, it will be seen that much of the data shows a near constant rate of gas slippage past the plunger, although some variations are seen. Figure 9 shows gas slippage as a function of velocity for Plunger No. 9.

The following shows how this may be explained.

Assume that near terminal velocity is reached (acceleration  $\cong 0$ ) and that friction is small over the short length of the plunger. This gives:

$$(P_b - P_f) A = W_t$$

where:  $P_b$  = pressure under plunger, psi

$P_f$  = pressure over plunger, psi

A = cross sectional area of plunger, sq. in.

$W_t$  = plunger weight, lbs

or

$$\Delta P = (P_b - P_f) = W_t/A$$

Note that this shows that the liquid slug size does not affect the amount of gas that comes upward across the plunger. Rather, it is only the change in pressure locally across the plunger that is present to cause gas flow. The slug size could influence the total gas passage by slowing down the plunger and liquid, which would then allow more total time for the gas to bypass the plunger, but the rate of gas passing the plunger should be unaffected directly by the slug size.

To quantify the gas slip past the plunger, assume that the gas is flowing according to the same parameters that cause gas to flow past an orifice. Then:

$$Q = C_D A_e \sqrt{\frac{\Delta P Z g}{\rho}}$$

where:  $\rho$  = gas density

$Q$  = volumetric flow rate of gas

$A_e$  = the effective annular area past the plunger

$C_D$  = effective discharge coefficient for flow across plunger

With constant temperature, the above can be reduced to the following proportionality, by placing  $Q$  in terms of standard conditions and showing density  $\approx$  pressure. Then:

$$Q_{s.c.} \approx K_1 \sqrt{\Delta P \cdot P} \approx K_1 \sqrt{\frac{W_t P}{A}}$$

$$\approx K_2 \sqrt{W_t P}$$

where:  $K_1, K_2$  = constants

$W_t$  = plunger weight

$P$  = pressure at which equation evaluated. The average of max and min casing pressure used in this report

Define the total gas bypassing the plunger over one trip up the tubing as VOL, evaluated at standard conditions. Then:

$$VOL = Q_{s.c.} \times t \approx K_2 \sqrt{W_t \cdot P} \times t$$

where:  $t$  = time to make one trip, Depth/Vel where: Vel = average velocity

Then, for the test well conditions:

$$\text{Vol} \cong K \frac{\text{Depth}}{\text{Vel}} \sqrt{\text{Wt} \cdot P}$$

If K is set to one and VOL is identified as total slip, then the grouping

$$\frac{\text{SLIP} \cdot \text{VEL}}{\text{Depth} \cdot \sqrt{\text{Wt} \cdot P}}$$

should be a correlating parameter for a plot of this grouping vs, say velocity for the test results. In other words, the experimental values inserted into this correlating group of parameters should give near constant values vs other changes in test results. Other unknown effects could come into play, but it would be expected that this grouping, used as a correlating parameter, should organize the data without a lot of scatter. The composite for all plungers tested is shown in Figure 13. While the slip function does plot in fairly straight lines, the correlations for various plungers have slopes instead of constant values, perhaps due to a changing "orifice coefficient" across the plunger as a function of velocity.




Figure 1 - Plunger lift laboratory test assembly




Figure 2 - Plunger fall test  
plunger No. 7 casing pressure 70 psig  
water load 10 gallons




Figure 3 - Plunger rise test  
plunger No. 7 casing pressure 80 psig  
water load 10 gallons




Figure 5 - Plunger rise test  
plunger No. 7 casing pressure 40 psig  
water load 10 gallons




Figure 4 - Plunger rise test  
plunger No. 7 casing pressure 60 psig  
water load 10 gallons




Figure 6 - Plunger rise test  
plunger No. 7 casing pressure 30 psig




Figure 7 - Plunger evaluation  
fallback correlation




Figure 8 - Plunger test  
no plunger - gas lift only 70 psig  
water load 10 gallons





Figure 9 - Plunger slip evaluation  
plunger No. 9








Figure 11 - Plunger field test  
Elkhorn B No. 3




Figure 12 - Plunger field test  
Elkhorn B No. 3




Figure 13 - Plunger evaluation slip correlation




Figure 14 - Pmin correction correlation

\*\*\*\*TO CONTINUE: ENTER --TO STOP: ENTER HX

\*\*\*\*\*  
 \*  
 \* NOTES FOR INTERPRETATION OF ABOVE OUTPUT \*  
 \*  
 \*\*\*\*\*

PLUNGER LIFT IS POSSIBLE AT CONDITIONS BETWEEN THE ABOVE REQUIREMENTS FOR CLR AND SHUTIN PRESSURE. ANY CONDITIONS ABOVE WHERE THE SHUTIN PRESS. IS ABOVE 900.AND THE CLR IS MORE THAN 10000. CAN BE PRODUCED BY PLUNGER LIFT--IF THE WELL GLR IS GREATER THAN THE REQUIRED CLR, GAS MAY BE VENTED WITH PLUNGER AT SURFACE.

\*\* EVEN IF CONDITIONS FOR GLR AND PRESSURE ARE SATISFIED, THERE MUST BE A PRODUCING TIME CALCULATED OR THE SHUT -IN TIME EXCEEDS CYCLE TIME AND PRODUCTION NOT POSSIBLE IF BELOW ASSUMPTIONS HOLD.

CAUTION\*\*\*--THE ASSUMPTION USED TO CALCULATE THE BUILDUP AND PRODUCING TIMES IS THAT THE WELL IS A TIGHT FORMATION WELL WHERE CHANGES IN BHP DO NOT AFFECT THE RATE GREATLY. IF THIS DOES NOT APPLY TO YOUR WELL, THE REQUIRED PRESSURES ARE STILL CORRECT BUT THE VALUES OF TIMES REQUIRED WILL BE LONGER THAN CALCULATED ABOVE.

Example Data File Generated from Interactive Input

| EXAMPLE FOR PLUNGER LIFT REPORT |                                                    |
|---------------------------------|----------------------------------------------------|
| 2                               | IDENTIFIER NUMBER FOR PLUNGER TYPE                 |
| 1.995                           | ( 1 ) I. D. OF TUBING, INCHES                      |
| 5.00                            | ( 2 ) I. D. OF CASING, INCHES                      |
| 100.                            | ( 3 ) SURFACE TUBING PRESSURE, PSI                 |
| 10000.                          | ( 4 ) WELL DEPTH , FT                              |
| 100.                            | ( 5 ) AVERAGE TEMPERATURE, DEG F                   |
| 100.                            | ( 6 ) AVG. GAS PRODUCTION ,MCF/D                   |
| 10000.                          | ( 7 ) WELL GAS/LIQUID RATIO SCF/BBL                |
| 900.                            | ( 8 ) SHUT-IN PRESSURE OF WELL,PSI                 |
| 300.                            | ( 9 ) LOW CSG P. LIMIT WITH PLUNGER AT SURFACE,PSI |

\*\*\*\*\*  
 \*  
 \* AMOCO PLUNGER LIFT DESIGN AND ANALYSIS PROGRAM \*  
 \*  
 \*\*\*\*\*

EXAMPLE FOR PLUNGER LIFT REPORT  
 \*\*\*YOUR INPUT VALUES ARE AS FOLLOWS\*\*\*

|                                   |        |
|-----------------------------------|--------|
| TBG (ID),INCHES, =                | 1.99   |
| CSC (ID),INCHES, =                | 5.00   |
| TBG PRESS,PSI, =                  | 100.   |
| DEPTH,FT =                        | 10000. |
| AVG. WELL TEMP,DEG F. =           | 100.   |
| ESTIMATED GAS PRODUCTION,MSCF/D = | 100.   |
| WELL GLR, SCF/BBL =               | 10000. |
| WELL SHUT IN PRESSURE,PSI =       | 900.   |
| LOW PRESSURE LIMIT FOR CSG,PSI    | 315.   |

\*\*\*\*\*  
 \*  
 \* REQUIRED GLR AND SHUT-IN PRESS --RECOMMEDED SHUT-IN AND PRODUCING TIMES \*  
 \*  
 \*\*\*\*\*

| SLUG SIZE<br>BBLs       | SHUT-IN TIME<br>TIME,MINS | PRODUCING TIME<br>MINUTES | SHUT-IN PRESS<br>REQ,D PSIA           | MINIMUM<br>REQ,D GLR,SCF/B |
|-------------------------|---------------------------|---------------------------|---------------------------------------|----------------------------|
| 0.10                    | 102.16                    | 0.0                       | 401.42                                | 79221.44                   |
| 0.35                    | 96.70                     | 0.0                       | 401.42                                | 21427.23                   |
| 0.60                    | 98.86                     | 0.0                       | 432.30                                | 12726.65                   |
| WELL GLR= 10000.        |                           |                           | CAN OPERATE AT LOWER REQUIRED GLRS -- | \\//                       |
| 0.85                    | 120.31                    | 2.09                      | 501.31                                | 9941.48                    |
| 1.10                    | 154.12                    | 4.28                      | 565.89                                | 8342.98                    |
| 1.35                    | 188.88                    | 5.52                      | 626.09                                | 7273.64                    |
| 1.60                    | 223.91                    | 6.49                      | 681.90                                | 6486.27                    |
| 1.85                    | 259.20                    | 7.20                      | 733.33                                | 5867.02                    |
| 2.10                    | 294.42                    | 7.98                      | 780.38                                | 5356.14                    |
| 2.35                    | 329.69                    | 8.71                      | 823.05                                | 4919.31                    |
| 2.60                    | 365.08                    | 9.32                      | 861.34                                | 4535.40                    |
| 2.85                    | 400.25                    | 10.15                     | 895.24                                | 4190.77                    |
| WELL SHUTIN PRESS= 900. |                           |                           | CAN OPERATE AT LOWER                  | /\\ \ REQUIRED PRESSURES   |
| 3.10                    | 435.44                    | 10.96                     | 924.76                                | 3876.20                    |
| 3.35                    | 470.57                    | 11.83                     | 949.90                                | 3585.29                    |
| 3.60                    | 505.87                    | 12.53                     | 970.66                                | 3313.47                    |
| 3.85                    | 540.84                    | 13.56                     | 989.03                                | 3066.26                    |

Figure 15